



2020

# NEW PRODUCTS

▶ **METS**



**SINCE  
1977**



**SINCE  
MORE THAN  
40 YEARS  
AT YOUR  
SERVICE**



## ACCESSORIES FOR INFLATABLE BOATS

ACCESSORIES AND SPARE PARTS FOR INFLATABLE BOATS

### ACCESSORIES AND SPARE PARTS FOR INFLATABLE BOATS



#### ALUMINIUM TELESCOPIC PADDLE

Mini telescopic light alloy paddle, with plastic blade and parts high visibility orange colour.  
Suitable for tenders and life rafts.

	Minimum length cm	Maximum length cm
<b>381141</b>	53	107
<b>381152</b>	63,5	137

### AIR PUMPS AND SPARE PARTS



#### VALVE FOR INFLATABLE BOATS

Valve with "push-push" opening and maximum seal thanks to its special silicon gasket, it can be used both for tubulars and for inflatable floors. Compact design with ergonomic cap equipped with safety lanyard.

##### Technical features

External diameter	62 mm
Internal diameter	37 mm
Built-in dimensions	38 mm

grey  
**583113**

black  
**583114**

### ACCESSORIES FOR ANCHORS AND CHAINS



#### S.STEEL AISI 316 CHAIN STOPPER

##### Technical features

For chain diameter	8 - 10 mm
Base dimensions	80 x 70 mm

**194164** Chain stopper made of **STAINLESS STEEL AISI 316** that allows to lighten the load of windlass preventing the anchor rode unwanted release while the boat is in use.

### ACCESSORIES AND SPARE PARTS FOR QUICK WINDLASSES AND CAPSTANS



#### CONTROL PANEL WCS810

##### Technical features

Length	77,2 mm
Width	77,2 mm
Protrusion	20,5 mm
Built-in dimensions	30 mm

**036611** Control panel for windlass (UP/DOWN).



#### SENSOR AND MAGNET CHAINCOUNTER FOR WINDLASS

**036643** Spare magnet and sensor kit for windlass.

## CHAIN STRIPPER FOR WINDLASS

Spare chain stripper for QUICK windlass

	Windlass model	Our windlass item number
<b>036675</b>	EAGLE E1	036300 - 036320 - 036330
<b>036677</b>	PRINCE DP1	036395 - 036400 - 036410
<b>036679</b>	RIDER R1	036420 - 036430



## ADAPTER FOR QUICK WINDLASS

Spare adapter for QUICK windlass.

	Model	Windlass from Watt
<b>036905</b>	TG40	300 - 500
<b>036910</b>	TG50	700 - 1000
<b>036915</b>	TG70	1500



## ENGINE FOR QUICK WINDLASS

Spare engine for QUICK windlass.

	ENGINE
<b>Technical features</b>	
Voltage	12 Volt

	Watt	Suggested adapter code
<b>036930</b>	300	036905
<b>036935</b>	500	036905
<b>036937</b>	700	036910
<b>036940</b>	1000	036910
<b>036945</b>	1500	039915



## ACCESSORIES AND SPARE PARTS FOR WINDLASSES AND CAPSTANS

### ANCHORING KIT

Kit composed of polyester rope and calibrated hot galvanised chain with splice.

	Ø rope mm	Rope length m	chain Ø mm	Chain length m
<b>036217</b>	12	50	6	10
<b>036218</b>	14	50	8	10



### STAINLESS STEEL CLEATS



#### S.STEEL AISI 316 CLEAT "POP-UP" MODEL RECESS FLUSH TO THE DECK

##### Technical features

Base dimensions	89 x 31 mm
Flush hole	22 mm

**210880** "POP-UP" cleat recessed flush to deck made of **STAINLESS STEEL AISI 316**.



#### S.STEEL AISI 316 CLEAT "HEAVY" MODEL

"HEAVY" cleat made of **STAINLESS STEEL AISI 316** mirror polished. To be fixed with studs.

	Length mm	Width mm	Height mm	Hole-to-hole distance mm	Thread
<b>211586</b>	160	47	35	55	M8
<b>211588</b>	200	60	45	65	M10

### PVC FENDER PROFILES






#### PROFILE FOR FLAT JUNCTION

PVC profile with rigid support for boats for flat junctions. To be fitted warm, with no screws or rivets.

FENDER PROFILE HEIGHT 35 mm

##### Technical features



Fiberglass thickness - application point	from 6 to 9 mm
Weight (approx.)	1440 gpm


	 black	 white	 grey
m			
12	<b>222301/12</b>	<b>222302/12</b>	<b>222303/12</b>
24	<b>222301/24</b>	<b>222302/24</b>	<b>222303/24</b>
48	<b>222301/48</b>	<b>222302/48</b>	<b>222303/48</b>

#### RIGID SUPPORT

**222030** "T" rigid support for profile 35 mm height. Bars of 2 meters.

#### END CAP

	 black	 grey
	<b>223430</b>	<b>223430G</b>



### STAINLESS STEEL FOLDABLE LADDERS



#### LADDER "SNOOPY" SERIES

**STAINLESS STEEL** foldable ladder for transom mounting, suitable for inflatable and small boats. Very practical since it is very tight but at the same time strong, fine, with accurate finishings.

	N. steps	Length cm	Width cm	hose Ø mm
<b>110142</b>	3	65	22	22
<b>110143</b>	3	80	20	25
<b>110144</b>	4	105	20	25
<b>110145</b>	4	90	22	22

## ADJUSTER ARMS AND SPRINGS FOR HATCHES

## STAINLESS STEEL AISI 316 GAS SPRING

**STAINLESS STEEL AISI 316** telescopic gas springs.  
Equipped with threaded connector for applying eye connectors on shaft.  
Standard eye connector on pipe.

## Technical features

Inner diameter 8 mm

	Length opened mm	Length closed mm	Response kg. Kg	Cylinder diameter mm	Eye diameter mm
<b>202079</b>	250	170	10	15	6
<b>202080</b>	250	170	20	15	6
<b>202082</b>	355	225	12	18	8
<b>202083</b>	355	225	20	18	8
<b>202084</b>	355	225	30	18	8
<b>202085</b>	375	230	20	18	8
<b>202086</b>	500	290	20	18	8
<b>202087</b>	500	290	40	18	8
<b>202088</b>	525	305	14	18	8
<b>202090</b>	525	305	30	18	8
<b>202094</b>	550	320	38	18	8
<b>202095</b>	550	320	64	18	8
<b>202096</b>	600	350	20	18	8
<b>202097</b>	600	350	30	18	8
<b>202098</b>	600	350	40	18	8




## ACCESSORIES FOR SAILING

## SAILGUARD SAIL SAVERS

## Technical features

Cordage diameter max 9 mm


- 201360** White nylon sail savers  
You can install them in a few seconds without removing the shrouds.  
Sold in pairs.




## AISII 316 STAINLESS STEEL SHACKLES

## AISII 316 STAINLESS STEEL BOW SHACKLE

	A - Ø mm	B mm	C mm	D mm
<b>190104</b>	4	8	25	15
<b>190105</b>	5	10	33	20
<b>190106</b>	6	12	38	24
<b>190108</b>	8	17	53	33
<b>190110</b>	10	22	66	41
<b>190112</b>	12	25	76	47
<b>190114</b>	14	29	90	57
<b>190116</b>	16	33	100	63
<b>190120</b>	20	38	128	77
<b>190122</b>	22	44	141	88
<b>190125</b>	25	50	155	100




### AISI 316 STAINLESS STEEL SHACKLE



	A - Ø mm	B mm	C mm	D mm
190204	4	8	24	15
190205	5	11	32	21
190206	6	12	40	25
190208	8	17	51	32
190210	10	20	66	42
190212	12	25	76	48
190214	14	30	88	54
190216	16	34	102	64
190218	18	37	110	69
190220	20	41	128	77
190222	22	45	141	88
190225	25	50	155	100

### AISI 316 STAINLESS STEEL LONG "D" SHACKLES




	A - Ø mm	B mm	C mm	D mm
190324	4	8	39	29
190325	5	10	50	38
190326	6	12	60	45
190328	8	15	83	64
190330	10	21	98	74
190332	12	24	120	96

## SNAP HOOKS

### SNAP HOOK WITH SCREWABLE RING NUT

STAINLESS STEEL AISI 316 snap hook with screw opening.



	Ø mm	Dimensions L1 x L2 x F mm
190603	3,5	36 x 17 x 5
190604	4	40 x 20 x 5,5
190605	5	49 x 23 x 6,5
190606	6	58 x 26 x 7,5
190608	8	75 x 34 x 10,5

### ALUMINIUM SNAP HOOK WITH EYELET

Anodized aluminium coloured snap hook with chromed eye and ring.




Ø mm	Length mm	10 pcs purple 190645V	10 pcs green 190647G	10 pcs blue 190646B	10 pcs red 190646R
5	50	-	-	-	-
6	60	-	-	190646B	190646R
7	70	-	190647G	-	190647R
8	80	-	-	-	190648R

## ACCESSORIES FOR S/S CABLES

### STAINLESS STEEL CABLE CLAMP

Clamps for naked or plastic-coated cables. They can be easily installed and removed, using simple fixed keys or manual tools.



RAIL CLAMP SINGLE	RAIL CLAMP DOUBLE	Dimensions L x L1 x H x B x D mm	Thread MA	For cable Ø mm
-	190743	18 x 36 x 14 x 6,5	M4	3
190734	190744	20 x 40 x 17 x 8,5	M5	4
190735	190745	25 x 50 x 15 x 11	M5	5
-	190746	30 x 60 x 23 x 13	M6	6
-	190748	36 x 72 x 27 x 18	M8	8

## HANDRAILS AND HANDLES

## STAINLESS STEEL HANDRAILS

STAINLESS STEEL handrail for boats. **Oval pipe** mirror polished.

	Length mm	Internal height mm	Tube diameter mm
<b>150037</b>	300	35	25 x 20
<b>150038</b>	400	35	25 x 20
<b>150039</b>	500	35	25 x 20
<b>150040</b>	600	35	25 x 20



## STAINLESS STEEL BASES AND FITTINGS

## "TEE" 90° CONNECTOR WITH EYE FOR SAILING LIFELINE

## Technical features

For pipe diameter 22 mm

**150368** "Tee" 90° connector with **STAINLESS STEEL AISI 316** eye for sailing lifeline mirror polished.



## S.STEEL AISI 316 ROUND BASE

Round base for pulpits **precision cast, STAINLESS STEEL AISI 316 MIRROR POLISHED.**

	For pipe Ø mm	Inclination	Base dimensions mm
<b>150563</b>	22	90°	66 x 16
<b>150566</b>	25	90°	75 x 16
<b>150573</b>	22	60°	66 x 13
<b>150576</b>	25	60°	80 x 16



## S.STEEL AISI 316 RECTANGULAR BASE

Rectangular base for pulpits **precision cast, STAINLESS STEEL AISI 316 MIRROR POLISHED.**

	For pipe Ø mm	Inclination	Base dimensions mm
<b>150583</b>	22	90°	78 x 44 x 16
<b>150586</b>	25	90°	78 x 44 x 16
<b>150593</b>	22	60°	78 x 44 x 13
<b>150596</b>	25	60°	78 x 44 x 14



## STAINLESS STEEL EYE BOLTS

## STAINLESS STEEL AISI 316 EYE BOLT

	Thread MA	Ø eye mm	Screw length mm
<b>190956</b>	6	5	60
<b>190958</b>	8	6	80
<b>190960</b>	10	8	100
<b>190962</b>	12	10	120



## STAINLESS STEEL AISI 316 MALE EYE BOLT

STAINLESS STEEL DIN 580 male eye bolt.

	Thread MA	Ø eye mm	Screw length mm
<b>191106</b>	6	6	14
<b>191108</b>	8	8	15
<b>191110</b>	10	10	19
<b>191112</b>	12	12	22
<b>191116</b>	16	16	27
<b>191120</b>	20	20	30
<b>191124</b>	24	24	36



## STAINLESS STEEL AISI 316 FEMALE EYE BOLT



	Thread MA	Ø eye mm
191126	6	6
191128	8	8
191130	10	10
191132	12	12
191136	16	16
191140	20	20
191144	24	24

## STAINLESS STEEL HINGES

### 90° ANGLE BRACKET S.S. AISI 316

STAINLESS STEEL AISI 316 angle bracket with 4 holes.



	Length mm	Width mm
143183	31	12
143184	46	13
143186	61	15

### 90° ANGLE BRACKET S.S. AISI 316

STAINLESS STEEL AISI 316 angle bracket with 6 holes.




	Length mm	Width mm
143194	41	25
143195	56	35
143198	80	50

## FLUSH MOUNT LATCHES FOR DOORS AND PANEL DOORS

### SPRING LOCK

#### Technical features

Length	58 mm
Flush hole	21 mm



**260315** STAINLESS STEEL lock with spring push-button and padlock eye.

## STAINLESS STEEL LEVER LATCHES

### STAINLESS STEEL AISI 316 LATCH

STAINLESS STEEL AISI 316 lever lock with 90° hook and padlock holder.




	Length mm	Width mm
201174	85	28
201175	100	30

## FLUSH MOUNT S.STEEL LIFTING PLATES

### STAINLESS STEEL AISI 316 LIFTING RING

STAINLESS STEEL AISI 316 lifting handle with spring lock.  
Item 200746 can be unlocked also from inside.




	Diameter mm	Recessed diameter mm	Total height mm
200745	44	38	35
200746	61	50,5	37

### STAINLESS STEEL AISI 316 LIFTING RING

#### Technical features

Dimensions	50 x 50 mm
Height	18 mm

- 200761** **STAINLESS STEEL AISI 316** square lifting plate mirror polished with threaded holes for fixing hidden screws.



### STAINLESS STEEL AISI 316 LIFTING RING

#### Technical features

Diameter	50 mm
Height	18 mm



- 200762** **STAINLESS STEEL AISI 316** round lifting plate mirror polished with threaded holes for fixing hidden screws.




## ACCESSORIES FOR BIMINI TOPS

### JOINT

Joint for deck mounting with pipe holder for bimini tops.

hole Ø mm	 10 pcs	 2 pcs blister
20	<b>127485</b>	<b>127485B</b>
22	<b>127486</b>	<b>127486B</b>



## TRIM TAB SYSTEMS


### STAINLESS STEEL TRIM TABS

**STAINLESS STEEL** pair of trim tabs reinforced with a built in special hinge mounted between the mobile and fixed part.  
Fitted with holes for the installation of actuators BENNET brand or others.

#### Technical features

Flaps rotation	180°
Flaps thickness	2 mm

	Dimensions		Boat length
	A mm	B mm	mm
<b>070224</b>	395	320	6 - 7
<b>070226</b>	450	320	7 - 8
<b>070228</b>	540	320	8 - 9
<b>070230</b>	620	320	9 - 10



### HYDRAULIC STEERING SYSTEMS



#### BRASS CONNECTOR FOR COPPER PIPES

Connector male	90° connector male	Connector female	90° connector female	Thread	For pipe Ø mm
-	-	<b>630466</b>	-	1/4"	6
<b>630448</b>	<b>630458</b>	<b>630468</b>	<b>630478</b>	1/4"	8
<b>630450</b>	<b>630460</b>	<b>630470</b>	<b>630480</b>	1/4"	10
-	-	<b>630472</b>	-	3/8"	6
-	-	<b>630474</b>	-	3/8"	8
<b>630451</b>	<b>630461</b>	<b>630475</b>	<b>630481</b>	3/8"	10
<b>630452</b>	<b>630462</b>	-	<b>630482</b>	3/8"	12
<b>630454</b>	-	-	-	1/2"	10
<b>630455</b>	-	-	<b>630483</b>	1/2"	12



#### BRASS CONNECTOR FOR COPPER PIPES

Connector "Tee"	90° connector	For pipe Ø mm
<b>630486</b>	<b>630496</b>	6
<b>630488</b>	<b>630497</b>	8
<b>630490</b>	<b>630498</b>	10
<b>630492</b>	<b>630499</b>	12



#### COPPER PIPE

Copper pipe sold per linear meter.

	Dimensions mm
<b>630438</b>	6 x 8
<b>630440</b>	8 x 10
<b>630442</b>	10 x 12

### PURIFYING FUEL FILTERS

#### FUEL FILTER

FILTER	
For inboard engines	Original codes references
OMC	174144
RACOR	S3214

- 297040** Universal water/fuel filter separator complete with varnished aluminium mounting bracket, ports with hose connectors, see-thru bowl and self-venting drain.  
10 micron 1" - 12UNF cartridge.

#### CARTRIDGE


#### Technical features

Height - H	103 mm
A	235 mm
B	70 mm
C	190 mm
D	100 mm
E	105 mm
D1	94 mm
D2	32 mm
D3	70 mm
Central screw thread	25 mm

- 297041** 10 micron 1" - 12UNF replacement cartridge for separating filter item 297040.

#### BOWL

- 297023** Transparent spare bowl complete with drain plug



#### FUEL FILTER FOR DIESEL ENGINES

FILTER	
<b>297043</b>	Universal water/fuel filter separator complete with varnished aluminium mounting bracket, ports with hose connectors, see-thru bowl and self-venting drain. 21 micron 11/16" - 16UNC cartridge.

#### CARTRIDGE

- 297044** 21 micron 11/16" - 16UNC replacement filter for separating filter item 297043.

#### BOWL

- 297045** Spare aluminium bowl with w/o-ring and drain plug.





### FUEL CONNECTORS

#### CONNECTOR FOR MERCURY - MARINER ENGINES

##### FEMALE CONNECTOR

###### Type

<b>300371</b>	Female connector MERCURY-MARINER suitable both fuel lines engine side and for fuel lines YAMAHA tank side.
<b>300382</b>	Female connector MERCURY-MARINER for fuel lines engine side double air-tight Silver model.
<b>300447</b>	Female connector for MERCURY-MARINER fuel lines.
<b>300378</b>	Female connector MERCURY for fuel line engine side - old type.
<b>300381</b>	Female connector MERCURY-MARINER for fuel lines engine side.
<b>300383</b>	Female connector MERCURY-MARINER for fuel line tank side.
<b>300384</b>	Female connector MERCURY-MARINER for fuel line tank side double air-tight Silver model.
<b>300440</b>	MERCURY female connector tank side for hoses 5/16" 10 mm.
<b>300445</b>	Female connector MERCURY. Tank side (latest models).

##### MALE CONNECTOR

###### Type

<b>300376</b>	Male connector MERCURY-MARINER tank side.
<b>300380</b>	Male connector MERCURY - MARINER for fuel line tank side.
<b>300385</b>	Male connector MERCURY-MARINER with valve for engines.
<b>300430</b>	Male connector MERCURY-MARINER "T" shaped to connect one tank with two engines and viceversa.
<b>300446</b>	Threaded male connector MERCURY tank side.
<b>300444</b>	Threaded male connector MERCURY tank side (latest models).



### ACCESSORIES AND SPARE PARTS FOR TANKS



#### 2-WAY MALE/FEMALE VALVE

<b>297071</b>	2-way male/female brass valve with 1/4" NPT thread.
---------------	---



## OIL FILTERS

## OIL FILTERS SCREW-TYPE FOR OUTBOARD ENGINES



## EVINRUDE - JOHNSON

	Original codes references	HP	D1 mm	D2 mm	D3 mm	H mm
<b>296700</b>	434839	10 - 15	65	3/4" - 16	62	60
<b>296703</b>	778885 - 5031441	25 - 30 - 40 - 50 - 60 - 70	65	3/4" - 16	62	50
<b>296715</b>	778888 - 5035703	200 - 225	65	3/4" - 16	62	90

## HONDA

	Original codes references	HP	D1 mm	D2 mm	D3 mm	H mm
<b>296720</b>	15400-PFB-004 / 15400-PFB-014 15400-ZW4-003 / 15400-PFB-007	8 - 9,9 - 20 - 25 - 30 - 35 - 40 - 45 - 50	68	M20 x 1,5	63	71
<b>296721</b>	15400-PFB-007 15400-FM1-F03	BF25, BF30, BF40 and BF50	66	M20 x 1,5	48	72
<b>296723</b>	15400-POH-305PE / 15400-POH-305 15400-ZJI-004 / 15400-PLM-A01PE	75 to 225	84	M20 x 1,5	63	84
<b>296726</b>	15400-RBA-F01	80 to 130	68	M20 x 1,5	61	87

## MERCURY

	Original codes references	HP	D1 mm	D2 mm	D3 mm	H mm
<b>296720</b>	35-822626Q03	8 - 9,9 - 15 - 20	68	M20 x 1,5	63	71
<b>296740</b>	35-822626Q2 / Q04 / Q05 / 35-8M0065103	25 - 30 - 40 - 45 - 50 - 60 - 75 - 80 - 90 - 115	65	M20 x 1,5	60	60
<b>296748</b>	35-822626Q15 / 35-822626T7	EFI 4S 225	79	3/4" - 16	72	78
<b>296745</b>	35-877761Q01 / 35-877761K01	80-100-115	90	M22 x 1,5	64	82
<b>296750</b>	35-877767K01 - 35-877767Q01	VERADO 4 CYL. (135 - 150 - 175 - 200)	72	M24 x 1,5	69	99
<b>296751</b>	35-877769Q01 - 35-877769K01	VERADO 6 CYL. (225 - 250 - 275 - 300 - 350)	72	M24 x 1,5	69	114

## NISSAN

	Original codes references	HP	D1 mm	D2 mm	D3 mm	H mm
<b>296721</b>	3R0076150M	9.9A - 9.9B - 9.9B2 - 9.9C - 15A - 15B - 15B2 - 15C - 18B - 18B2 - 20C - 25A - 25B - 30A - 30B	66	M20 x 1,5	48	72

## SELVA

	Original codes references	HP	D1 mm	D2 mm	D3 mm	H mm
<b>296740</b>	-	25 - 40 - 60 - 80 - 90 - 115	65	M20 x 1,5	60	60
<b>296720</b>	5GH-13440-00	9,9 to 115	68	M20 x 1,5	63	71

## SUZUKI

	Original codes references	HP	D1 mm	D2 mm	D3 mm	H mm
<b>296703</b>	16510 - 87J00	25 - 30 - 40 - 50 - 60 - 70	65	3/4" - 16	60	62
<b>296715</b>	16510 - 93J00	150 - 175 - 200 - 225 - 250	68	3/4" - 16	62	91

## YAMAHA

	Original codes references	HP	D1 mm	D2 mm	D3 mm	H mm
<b>296729</b>	3FV-13440-00 / 3FV-13440-30	F15, F25, F40, F50, F80, F100 and T50 (from 1995 up to 2000)	66	M20 x 1,5	51	73
<b>296740</b>	5GH-13440-20	9,9 - 100	65	M20 x 1,5	60	60
<b>296720</b>	5GH-13440-00	9,5 - 15 - 25 - 30 - 40 - 60 - 75 - 90 - 100 - 115	68	M20 x 1,5	63	71
<b>296721</b>	5GH-13440-70	F115, F75, F90 and LF115	66	M20 x 1,5	48	72
<b>296748</b>	69J-13440-00	150 - 200 - 225 - 250	79	3/4" - 16	72	78
<b>296726</b>	N 26-13440-00	225 - 250	72	M20 x 1,5	64	87

## TOHATSU

	Original codes references	HP	D1 mm	D2 mm	D3 mm	H mm
<b>296740</b>	3R007-6150M	8 - 9 - 30	65	M20 x 1,5	60	60



# PROPELLERS

AMITA 3 ALUMINIUM PROPELLERS- 4

## AMITA 3 ALUMINIUM PROPELLERS- 4

### SOLAS AMITA 3 BLADES ALUMINIUM PROPELLERS - T5 GROUP

DIAMETER - PITCH	7,80 X 6	7,80 X 7	7,80 X 8	7,80 X 9	CODE MULTI-FIT KIT
PROPELLERS CODE	711286	711287	711288	711289	
JOHNSON - EVINRUDE	4 and 6 (4S) from 2011				NO KIT
MERCURY	4hp,5hp,6hp (4T from 2011 onwards)				NO KIT
TOHATSU	5 (2S) 4, 5 and 6 (4S)				NO KIT

### SOLAS AMITA 3 BLADES ALUMINIUM PROPELLERS - OA GROUP

DIAMETER - PITCH	9,25 X 7	9,25 X 8	9,25 X 9	9,25 X 10	9,25 X 11	9,25 X 12	CODE MULTI-FIT KIT
PROPELLERS CODE	711427	711428	711429	711430	711431	711432	
JOHNSON - EVINRUDE	9.9 and 15 (2S) 9.9~15 (4S up to 2001)						NO KIT

### SOLAS AMITA 3 BLADES ALUMINIUM PROPELLERS - YA GROUP

DIAMETER - PITCH	9,25 X 7	9,25 X 8	9,25 X 9	9,25 X 10	9,25 X 11	9,25 X 12	CODE MULTI-FIT KIT
PROPELLERS CODE	724007	724008	724009	724010	724011	724012	
YAMAHA	9.9, 15 (2 STROKE) 9.9 (4S up to 2007), 15, 20 (4S)						NO KIT
HONDA	9.9A, 15A, 8D, 10D, 15D, 20D						NO KIT
SELVA	9.9 (up to 2007) 15, 20 (WAHOO 4S)						NO KIT
PARSUN	F-9.9 FWL, F-15 BML						NO KIT

### SOLAS AMITA 3 BLADES ALUMINIUM PROPELLERS - MA GROUP

DIAMETER - PITCH	9,25 X 8	9,25 X 9	9,25 X 10	9,25 X 11	CODE MULTI-FIT KIT
PROPELLERS CODE	724018	724019	724020	724021	
MERCURY	6, 8, 9.9, 10, 15 (2S) 9.9, 15 (4S up to 2006)				NO KIT

### SOLAS AMITA 3 BLADES ALUMINIUM PROPELLERS - TA GROUP

DIAMETER - PITCH	9,25 X 8	9,25 X 9	9,25 X 10	9,25 X 11	9,25 X 12	CODE MULTI-FIT KIT
PROPELLERS CODE	724038	724039	724040	724041	724042	
TOHATSU	9.9, 15, 18 (2S - 4S)					NO KIT
MERCURY	9.9 BIG FOOT (4S from 2007 until today) 15, 20 (4S from 2007 until today)					NO KIT
JOHNSON -EVINRUDE	15HP R4/R14/15HP TE/TEL/PL (4S), 15HP 4S from 2011					NO KIT

### SOLAS AMITA 3 BLADES ALUMINIUM PROPELLERS - YB GROUP

DIAMETER - PITCH	9,90 X 9	9,90 X 10	9,90 X 11	9,90 X 12	9,90 X 13	CODE MULTI-FIT KIT
PROPELLERS CODE	724209	724210	724211	724212	724213	
YAMAHA	20 (2S), MARINER 30 (2S) 25(2S - 4S)					NO KIT
SELVA	25 (4S MORAY - 4S KINGFISH)					NO KIT
PARSUN	F-20 BMS/BML, F-25 BMS/BML					NO KIT

### SOLAS AMITA 3 BLADES ALUMINIUM PROPELLERS - TB GROUP

DIAMETER - PITCH	9,90 X 10	9,90 X 11	9,90 X 12	9,90 X 13	CODE MULTI-FIT KIT
PROPELLERS CODE	724310	724311	724312	724313	
HONDA	25, 30				NO KIT
TOHATSU	25, 30 (2S - 4S) MAXI (2S)				NO KIT
MERCURY	25, 30 (4S from 2007)				NO KIT

### SOLAS AMITA 3 BLADES ALUMINIUM PROPELLERS - OB GROUP

DIAMETER - PITCH	10,50 X 11	10,30 X 12	10,10 X 13	10 X 14	CODE MULTI-FIT KIT
PROPELLERS CODE	724421	724422	724423	724424	
JOHNSON - EVINRUDE	20, 25, 30 and 35 (2S) 25, 30 EVINRUDE E-TEC				NO KIT
SELVA	ANTIBES 20 XS, ANTIBES 25/30, MAIORCA 35				NO KIT

# PROPELLERS

AMITA 3 ALUMINIUM PROPELLERS- 4



## SOLAS AMITA 3 BLADES ALUMINIUM PROPELLERS - YC GROUP

DIAMETER - PITCH	12,10 X 9	11,80 X 10	11,60 X 11	11,40 X 12	11,10 X 13	11,10 X 14	11 X 15	11 X 17	CODE MULTI-FIT KIT
PROPELLERS CODE	724509	724510	724511	724512	724513	724514	724515	724517	
YAMAHA	40, 50, 55, 60 (from '91), TOP 700 (2S) 30 e 40 (3 Cyl. 4S), 40 (4 Cyl. 4S), 50, 60 (4S)								NO KIT
MERCURY	40, 50, 60 (2S) 30, 40, 50, 60 (4S)								722501
JOHNSON - EVINRUDE	40, 50, 60 (4S)								NO KIT
SUZUKI	40, 50, 55, 60, 65 (2S) 40, 50, 60 (4S)								NO KIT
HONDA	40, 50, 60								NO KIT
SELVA	MANTA40, BARRACUDA 40/50, 40 EFI (4S), ARJANA 747cc, 40/60 EFI (4S), DORADO 996 cc								NO KIT
TOHATSU	40, 50, 60 (2S - 4S), CORSA (2S) - MERCURY 40XR (2S), BFT60								722508

## SOLAS AMITA 3 BLADES ALUMINIUM PROPELLERS - YD GROUP

DIAMETER - PITCH	13,75 X 13	13,50 X 14	13,50 X 15	13,25 X 17	13 X 19	13 X 21	CODE MULTI-FIT KIT
PROPELLERS CODE	724713	724714	724715	724717	724719	724721	
YAMAHA	60 (year '92), 70, 75, 90, 100, 115, 130, 140 (2S) 40G, 70, 80, 90, 100, 115 (4S)						NO KIT
MERCURY	F40EFI PRO NEW, 40 BIG FOOT, 75, 80, 90, 100, 115, 125 (2S - 4S)						722502
HONDA	75, 90, 80 new, 100 new, 115 (up to 2009), 130						722515
SELVA	40/60 EFI MURENA, 80/100 EFI MARLIN, 115 NARWHAL, 115 EFI TARPON						NO KIT
TOHATSU	70 (from '99 to 2002), 75, 90, 115, 120, 140 (up to 2002) BFT 75, 90, 115 (from 2003) use KIT TD-RBKT our code 722509						NO KIT

## SOLAS AMITA 3 BLADES ALUMINIUM PROPELLERS - S14 GROUP

DIAMETER - PITCH	13,87 X 17	13,87 X 19	13,87 X 21	CODE MULTI-FIT KIT
PROPELLERS CODE	724827	724829	724831	
SUZUKI	70 from 2012, 80, 90, 100, 115 and 140 (4 S)			NO KIT
JOHNSON - EVINRUDE	90,115,140 (4 S)			NO KIT


## SOLAS AMITA 4 BLADES ALUMINIUM PROPELLERS - MA GROUP - High Thrust

DIAMETER - PITCH	10 X 5	10 X 7	CODE MULTI-FIT KIT
PROPELLERS CODE	725015	725017	
MERCURY	6 and 8 (2S) 9.9 and 15 (2S) 9.9, 15 (4S up to 2006)		NO KIT

## SOLAS AMITA 4 BLADES ALUMINIUM PROPELLERS - TA GROUP - High Thrust

DIAMETER - PITCH	10 X 5	10 X 7	CODE MULTI-FIT KIT
PROPELLERS CODE	725025	725027	
JOHNSON - EVINRUDE	15hp R4 /RL4 (4S) 15hp TE/TEL/PL (4S) (15hp 4S from 2011)		NO KIT
MERCURY	15 and 20 (4S from 2007 onwards) 9.9 Big Foot (4T from 2007 onwards)		NO KIT
TOHATSU	9.9, 15 and 18 (2S and 4S) 15 and 20 (4S)		NO KIT

### COUNTER-ROTATING PROPELLERS



## VOLVO PENTA COUNTER-ROTATING PROPELLERS

Counter-rotating for engines:

- Volvo Penta series DP 280
- Volvo Penta 290 Drive A - B - C.

\* Use original nuts.  
PLEASE NOTE : YOU CAN'T INSTALL ORIGINAL PROPELLERS IN COUPLE WITH SOLAS PROPELLERS.

## ALUMIMIMIUM COUNTER-ROTATING PROPELLERS

	Code OEM Volvo Penta	Couple	Left Front	Right Rear
	A3	7300A3	730F17	730R17
	A4	7300A4	730F17	730R19
	A5	7300A5	730F19	730R19
	A6	7300A6	730F19	730R21
	A7	7300A7	730F21	730R21
	B3	7300B3	730F17	730R17
	B4	7300B4	730F19	730R19
	B5	7300B5	730F19	730R21
	B6	7300B6	730F21	730R21

## STAINLESS STEEL COUNTER-ROTATING PROPELLERS

	Code OEM Volvo Penta	Couple	Left Front	Right Rear
	C2	7300C2	730CF15	730CR15
	C3	7300C3	730CF17	730CR17
	C4	7300C4	730CF19	730CR19
	C5	7300C5	730CF19	730CR21
	C6	7300C6	730CF21	730CR21
	C7	7300C7	730CF23	730CR23

## ISOTHERM FREEZERS AND REFRIGERATORS

## FRAME FOR FLUSH MOUNT FOR ISOTHERM CRUISE CLASSIC SERIES REFRIGERATORS

Finishing frame for flush mount installing of ISOTHERM refrigerators CRUISE CLASSIC line.  
Black colour.

	For refrigerator model	N. sides
<b>642843</b>	CRUISE CR42/V - CR49/V	3
<b>642856</b>	CRUISE CR65/V	3
<b>642861</b>	CRUISE CR85/V	2
<b>642886</b>	CRUISE CR130/EN - CR90/V	3



## WAECO "COOLMATIC CRX" COMPRESSOR REFRIGERATOR / FREEZER

## WAECO CoolMatic CRX-140 REFRIGERATOR

## Technical Features

Internal capacity	130 lts (including 11 lts freezer compartment)
Voltage	12/24 Volt
Average power consumption	65 Watts approx
Average power consumption with more than +25°C room temperature	1,9 Ah/h
External dimensions	525 x 620 x 815h mm
Weight	30 kg

## REFRIGERATOR

**642615** Waeco CoolMatic CRX-140 refrigerator.

## FRAME

Standard installation	Flush-mount installation
<b>642617</b>	<b>642618</b>

CE



## WAECO CoolMatic CRD-50 REFRIGERATOR

## Technical Features

Internal capacity	38,5 lt (6 lt freezer compartment included)
Voltage	12/24 Volt
Average power consumption	40 Watt approx
Average power consumption with more than +25°C room temperature	1,5 Ah/h
External dimensions	380 x 500 x 534h mm
Weight	17 kg

## REFRIGERATOR

**642535** Waeco CoolMatic CRD-50 drawer refrigerator.

## FRAME

Standard installation	Flush-mount installation
<b>642552</b>	<b>642553</b>



CE

## WAECO CoolMatic CRX-65D REFRIGERATOR

## Technical Features

Internal capacity	57 lt (7 lt freezer compartment included)
Voltage	12/24 Volt
Average power consumption	45 Watt approx
Average power consumption with more than +25°C room temperature	1,14 Ah/h
External dimensions	545 x 448 x 525h mm
Weight	20 kg

## REFRIGERATOR

**642546** Waeco CoolMatic CRX-65D drawer refrigerator.

## FRAME

Standard installation	Flush-mount installation
<b>642567</b>	<b>642568</b>




CE

## RIGID PLASTIC WATER TANKS

### EPDM GASKETS FOR FEMALE THREAD

EPDM flat gasket suitable for **FEMALE** thread.


	Internal thread G (inch - mm)	Internal diameter D mm	Thickness S mm
<b>249090</b>	1/4" - 11,4	5,5	2,5
<b>249091</b>	3/8" - 14,9	7,5	2,5
<b>249093</b>	1/2" - 18,6	10,5	2,5
<b>249094</b>	3/4" - 24,1	15,5	2,5
<b>249095</b>	1" - 30,2	21	2,5
<b>249096</b>	1" 1/4 - 39,8	26,5	2,5
<b>249097</b>	1" 1/2 - 44,8	32,4	2,5
<b>249098</b>	2" - 56,6	42,6	2,5



### EPDM GASKETS FOR MALE THREAD

EPDM flat gasket suitable for **MALE** thread.

	External thread G1 (inch - mm)	Internal diameter DN mm	Thickness S mm
<b>249124</b>	1/2" - 20,9	21	3,5
<b>249125</b>	3/4" - 26,4	26,5	3,5
<b>249126</b>	1" - 33,2	33,3	3,5
<b>249127</b>	1" 1/4 - 41,9	42	4,5
<b>249128</b>	1" 1/2 - 47,8	47,9	4,5
<b>249129</b>	2" - 59,6	59,7	4,5



### NBR O-RING

NBR O-Ring suitable for **MALE** thread.

	External thread G1 (inch - mm)	Internal diameter DN mm	Thickness S mm
<b>249154</b>	1/2" - 20,9	17,96	2,62
<b>249155</b>	3/4" - 26,4	23,47	2,62
<b>249156</b>	1" - 33,2	29,82	2,62
<b>249157</b>	1" 1/4 - 41,9	37,69	3,53
<b>249158</b>	1" 1/2 - 47,8	44,04	3,53
<b>249159</b>	2" - 59,6	55,56	3,53



### O-RING BOX

#### Technical features

Hardness

70 Shore

**750655**

Box with assortment of 407 o-ring nitrile gaskets with different diameters (from 1/8" to 2").



## ELECTRIC TOILETS

### LAGUNA ELECTRIC TOILET

New design electric toilet, compact with internal dimensions of a standard toilet. Bowl made of high quality ceramic and "Soft Close" lid. All the metallic parts and the screws are made of **STAINLESS STEEL** and the base is in shock-proof material. Fitted for mounting both on and under the deck. Equipped with a special self priming pump up to 1,50 mt (vertical) that allows the drainage up to 3,5 mt of height. Remote control included.

#### Technical features

Width	340 mm
Depth	405 mm
Height	410 mm
Height in open position	720 mm

	Volts	Amp
<b>601017</b>	12	24
<b>601018</b>	24	12

#### SPARE PART

**601019** Gaskets kit and spare valves for electric toilet item n. 601017 - 601018.



## ACCESSORIES FOR TOILETS

### EVOLUTION KIT FOR WC

Electric toilet conversion kit, silent and compact design. The kit includes base with discharge connector adjustable at 360°, pump, macerator pump, control panel and connectors.

The kit is compatible with the following Wc brands:

- Motomarine
- Jabsco
- TMC
- Raritan
- RM69
- Johnson Pump
- Lalizas
- ThetFord.

	Volts
<b>601047</b>	12
<b>601048</b>	24

#### SPARE PART

**601049** Gaskets kit and spare valves for kit Evolution for WC conversion suitable for our items 601047 and 601048.



### WASTE WATER PUMP

New pump designed for different uses:

- for waste water (complete with 90° connectors)
  - for household waste waters (complete with straight connectors)
  - bilge pump (complete with straight connectors).
- It can be used also in waste water tank for unloading operations of the same. The pump's body can rotate at 360° and can run dry without damage. Without impeller, it includes a NBR diaphragm for the maximum noiselessness. Equipped with double non return valve (one for each side).



	Use	Volts	Amperage Amp	Load capacity lt/min	Load capacity with 1,5 m head lt/min	hose Ø mm	Dimensions mm
<b>250502</b>	household waste waters	12	4,5	22	18	19 - 25	305 x 195 x 125
<b>250503</b>	household waste waters	24	2,5	22	18	19 - 25	305 x 195 x 125
<b>250504</b>	waste waters	12	6	32	26	38	355 x 195 x 125
<b>250505</b>	waste waters	24	3	32	26	38	355 x 195 x 125

### SUBMERSIBLE BILGE PUMPS

#### SUBMERSIBLE BILGE PUMP



Electric bilge pump with shockproof ABS housing, corrosion and electrolysis resistant.

	Model	Voltage Volts	Max flow rate lt/min	Consumption Amp	Fuse max Amp	Height mm	base Ø mm	Ø hose fitting inches - mm	Head m
600490	UP 500	12	32	2,5	5	94,5	50	3/4 - 19	4
600492	UP 1000	12	63	4	10	124,7	78	1 1/8 - 28,6	4
600494	UP 1500	12	95	10	20	160	96	1 1/16 - 26,5	4
600496	UP 2000	12	126	12	25	200	96	1 1/4 - 31,80	4
600497	UP 2000	24	126	6	15	200	96	1 1/4 - 31,80	4
600498	UP 3700	24	233	6	10	202	110	1 1/2 - 38	5

### "SEAFLO" AUTOMATIC WATER PRESSURE SYSTEM PUMP

#### BILGE PUMP WITH AUTOMATIC FLOW AND PRESSURE REGULATION

Self priming water system pump with automatic regulation of both pressure and flow rate reducing the consumption.

A built in by-pass valve reduces pulsation and the pump is much more silent. This water system pump is equipped with rubber bases against corrosion and noise, thermal protector that prevents overheating and can run dry without damage.

Diaphragms are made of Santoprene and grant a constant and silent flow.

Supplied complete with filter and hose connectors.

Tested in compliance with CE RoHS Community regulations.



	Model	N° diaphragm	Volts	Load capacity lt/min - GPM	Max power consumption Amp	Blocking pressure PSI - Bar	Dimensions mm
600204	42	4	12	11,3 - 3,0	7,5	55 - 3,8	202,5 x 125 x 111
600207	51	5	12	15,0 - 4,0	13	60 - 4,2	221,5 x 146 x 132
600208	51	5	12	18,9 - 5,5	8	60 - 4,2	221,5 x 146 x 132

## WATER PRESSURE SYSTEM PUMPS

### WATER PRESSURE SYSTEM PUMP WITH ELECTRONIC SENSOR

Self priming electric pump with **PTFE helicoidal gears**, non return valve and electronic control. Nickel brass body and connectors, **STAINLESS STEEL shaft**. Can be used as water system pressure pump, shower system for yachts, inflatable boats and campers.

#### MAIN FEATURES:


- Constant pressure, current and voltage control;
- The engine works progressively to reach the required flow rate;
- Expansion vessel not required;
- Reduced noise.



	Model	Volts	Load capacity lt/min	Max pressure Bar - PSI	Priming m	Fuse Amp	Ø ports	Filter	Panel
<b>600215</b>	UP 2/E	12 - 24	10	2 - 29	1	75	3/8"	-	-
<b>600216</b>	UP 3/E	12 - 24	15	2 - 29	1,5	15	3/8"	YES	-
<b>600217</b>	UP 6/E	12 - 24	26	2,5 - 36	2	20	1/2"	YES	-
<b>600218</b>	UP 14/E	12 - 24	46	2,5 - 36	3	30	3/4"	YES	YES

### WATER PRESSURE SYSTEM PUMP WITH EXPANSION VESSEL

Water system pump complete with accumulator tank for the best performances, ultra-silent with stable and constant flow. Self-priming capacity higher than the standard one, sufficiently powerful to supply until 3 users. Can run dry without damage with integrated and adjustable pressure switch. Tested in compliance with European legislation CE and RoHS.



	Voltage Volts	Load capacity lt/min - GPM	Priming m	Expansion vessel capacity lt	Blocking pressure PSI - Bar	Consumption Amp	Hose connector	Weight Kg
<b>600300</b>	12	11,3 - 3,0	1,80	0,75	45 - 3,1	11	1/2"	3,2

### WASHDOWN PUMPS

#### WASHING PUMP WITH ACCESSORIES KIT

##### Technical features

Voltage	12 Volt
Load capacity	17 lt/min - 4.5 GPM
Blocking pressure	70 PSI - 4,8 bar

#### 600175

Kit complete with: self-priming wash down pump with automatic regulation both of the flow rate and pressure, 6 mts coiled wash down hose U.V. resistant, 2 mt hose for water inlet, spray nozzle, 2,4 mt cable with cigarette lighter plug and connectors. Easy to use and to transport thanks to its handy carrying case supplied.

Thanks to the by-pass valve the pulsating effect is minimized and the pump is much more silent. Ideal for washing boats, livewell tanks, inflatable boats, caravans and mobile homes.

**Tested in compliance with european CE and RoHS regulations.**




CE

#### WASHING DOWN PUMP WITH ELECTRONIC CONTROL

Wash down kit includes:

- automatic self-priming electric pump, **equipped with helical PTFE gears**, in-line filter, nickel plated brass body and non-return valve.
- 15 m retractable hose and spray nozzle with quick connection, jet stop, check valve and trigger with flow regulation.

Recommended for yachts, inflatable boats, sailing boats for washing operations either with salt or fresh water.



CE



	Model	Voltage Volts	Load capacity lt/min	Pressure PSI - Bar	Priming m	Consumption Amp	Engine Watt	Fuse Amp	hose Ø mm	Ø ports	Weight Kg
<b>600197</b>	DP3/E	12/24	14	43,5 - 3	1,5	10	150	15	13	3/8"	4,6
<b>600199</b>	DP12/E	12/24	15	87 - 6	3	24	360	25	13	3/8"	5,5

### DECK POWER SUPPLY PRODUCTS

#### MARINCO DECK POWER CABLE WITH SOCKET

##### Technical features

Length	15 m
Thickness	3,3 mm <sup>2</sup> (12/3)

#### 641809

Power cable MARINCO (32 A - 220 V) with pre-mounted connector (item 641785) with LED light that indicates power on and protective cover, with straight blade male side.



CE



### FUSES AND FUSE HOLDERS

#### MINIVAL BLADE FUSE

MINIVAL blade fuses.

##### Product's features

Dimensions 11 x 16 x 3 mm

Amp	 50 pieces	 blister 10 pcs moq 10 blisters	Colour
3	<b>630923</b>	<b>630923B</b>	purple
4	<b>630924</b>	<b>630924B</b>	pink
5	<b>630925</b>	<b>630925B</b>	beige
7.5	<b>630927</b>	<b>630927B</b>	brown
10	<b>630929</b>	<b>630929B</b>	red



CE

### DOWN-LIGHTS

#### 6 LED INDOOR LIGHT

##### DOWN-LIGHT

##### Technical features

Led numbers	6
<b>Power</b>	<b>12 V</b>
External diameter	65 mm
Recessed diameter	57 mm
Total thickness	14,7 mm
Flush mount thickness	12,4 mm
Colour temperature	Warm light: 3000° K Cold light : 4000° K

Warm light	Cold light
<b>639690</b>	<b>639691</b>

##### POWER TRANSFORMER

**639645** Power transformer SNP15-12VF with a primary 200-240V AC connection and a 12V DC secondary one for maximum 1.25 Amp.

##### CONNECTOR

Connector for the connection of more lights to the same power transformer.

	N. users
<b>639647</b>	4
<b>639648</b>	6
<b>639649</b>	12



### COURTESY LIGHTS

#### 9-LED ROUND COURTESY LIGHT

9-led courtesy round light with external 180° or 360° lighting. ABS body and **STAINLESS STEEL** cover.

##### Technical features

Led numbers	9
<b>Power</b>	<b>12 VDC</b>
Power	9 x 0,10 Watt
Thickness	10,5 mm

Light angle	Diameter mm	Led colour	
		white	blue
180°	42	<b>639104</b>	<b>639105</b>
360°	40,1	<b>639106</b>	<b>639107</b>



CE



### 9-LED SQUARE COURTESY LIGHT

9-led courtesy square light with side or central lighting. ABS body and **STAINLESS STEEL** cover.

#### Technical features

Led numbers	9	
Power	12 VDC	
Power	9 x 0,10 Watt	
Dimensions	45,3 x 45,3 mm	
Thickness	10,5 mm	

Light angle	Led colour	
	white	blue
<input checked="" type="checkbox"/> central round light	639110	639111
<input type="checkbox"/> lower single light	639113	639114
<input type="checkbox"/> double side light	639117	639118

CE

## FLASHLIGHTS



### "OLIMPICA" LED COB 360° FLASHLIGHT

#### Technical features

Lighting	LED COB
Voltage	3 AA size (our item n.641254 included)
Brightness	At 360° 400 lumens At 180° 200 lumens 400 lumens strobe light
Autonomy	At 360° approx 4 hours At 180° approx 7 hours Approx. 4 hours of strobe light

**641152** LED COB flashlight with aluminium high resistance and powerful magnet on the base to fix it. Equipped with three different brightness settings:

- 360°
- 180°
- Stroboscopic.



### RECHARGEABLE LED LANTERN WITH BRIGHTNESS SETTINGS

#### Technical features

Voltage	4 Volt - 1,6 Ah (rechargeable battery included)
LED numbers	1 COB x 8 Watt
Brightness	550 lumens maximum intensity 150 lumens medium intensity
Charge time	20/24 hours
Autonomy	Approx 20 hours medium intensity Approx 1 hour of maximum intensity

**641167** ABS Led rechargeable lantern with different brightness settings. Thanks to its design it can be set up a tabletop or hanging lantern with its built in hook. Complete with recharge 220 V cable.



### "DIVING" UNDERWATER LED FLASHLIGHT

#### Technical features

Lighting	1 LUXEON TX WHITE
Voltage	4 AA size (our item n. 641254 included)
Protection	IP6X
Brightness	330 lumens
Autonomy	Approx 4,5 hours
Weight	422 g (with batteries)

**641181** Underwater LED flashlight with wide angle torch lens and reflector for diffused lighting. ABS body with anti-grip external finishing and ergonomic handle to ensure a safe grip underwater. Equipped with big size power switch to operate even with diving gloves and safety yarn thus avoiding accidental loss. Ideal for underwater photography.

### RECHARGEABLE "SURVIVAL" LED FLASHLIGHT WITH POWERBANK AND KNIFE

#### Technical features

Lighting	1 LED OSRAM P8
Voltage	Li-Ion 18650 - 3,7 V - 2,2 Ah (rechargeable)
Input/Output USB charge	5V - 1Amp
Protection	<b>IP4X WATERPROOF and water splashes</b>
Brightness	400 lumens maximum intensity 40 lumens medium intensity 400 lumens strobe light
Autonomy	Approx 2,5 hours maximum intensity Approx 13 hours of medium intensity Approx 2,5 hours of strobe light
Dimensions	128 x Ø25 mm

- 641184** LED flashlight with aluminium high resistance body. Thanks to its distinctive trait, this flashlight offers three solutions in one object:
- knife with easy-foldable blade made of **STAINLESS STEEL** 85 mm;
  - PowerBank 2200 mAh with USB cable for electronic devices recharge;
  - LED torch with adjustable intensity and stroboscopic light.



### HIGH BRIGHTNESS LED FLASHLIGHT

#### Technical features

LED numbers	1 COB
Voltage	3 AA size (our item n.641254 included)
Protection	<b>IP4X WATERPROOF and water splashes</b>
Brightness	200 lumens
Autonomy	4,5 hours
Light capacity	20 m
Dimensions	195 x 35 mm

- 641187** LED flashlight with ABS high resistance body and external finishing "Grip Film" anti-grip and rubber effect. Ideal for hands-free works because it offers the double possibility to hang thanks to the presence of a magnet on the back side for metallic surfaces and a pivoting flush hook.



### "TANGO SLIM" LED COB LIGHT RECHARGEABLE WITH SWIVELING BASE.

#### Technical features

LED numbers	1 COB x 5 Watt
Voltage	Li-Ion 18650 - 3,7 V - 1,8 Ah (rechargeable)
Brightness	250 lumens
Autonomy	2 hours approx
Charge time	4 hours approx

- 641191** "TANGO Slim" rechargeable LED COB light with magnetic 360° swiveling base and reclinable hanging hook. On the lamps's body there's a push button dimmer switch to adjust the light's brightness and it is equipped with USB charge cable included in the box.



### ADJUSTABLE LIGHTS



CE

#### SEARCHLIGHT ADJUSTABLE FROM INSIDE

##### Technical features

Voltage	12 Volt
Power	55 Watt
Light diameter	100 mm
Ext. Height from deck	203 mm
Internal protrusion	130 mm

**638983** Search light with halogen lamp, manually adjustable with handle from under deck or under roll-bar. Horizontal rotation at 340° and vertical (high and low) at 70°. **STAINLESS STEEL** case.



#### 24-LED HIGH BRIGHTNESS SPOTLIGHT

24-LED high brightness spotlight, **WATERPROOF** IP67. Made of die cast alluminium with **STAINLESS STEEL** bracket and polymethylmethacrylate lens.

##### Technical features

Led numbers	24
<b>Power</b>	<b>10 - 30 VDC</b>
<b>Protection</b>	<b>IP67</b>
Lighting cone	30°
Consumption	24 x 1W
Power	24 Watt
Luminous intensity	2400 Lumen
Endurance	50.000 hours

● black  
**639015**

○ white  
**639016**



CE

#### SEARCHLIGHT FOR ROLL BAR

##### Technical Features

Voltage	12 Volt
Power	55 Watt
Dimensions	117 x 115 x 88 mm

**638952** Spotlight for roll bar adjustable in vertical sense, white ABS with **STAINLESS STEEL** base.

### BRACKETS AND ACCESSORIES FOR ANTENNAS



#### INSTALLATION KIT FOR GPS/FISHFINDER

##### KIT

##### Technical features

Bracket dimensions	160 x 80 mm
Height	53,5 mm

**629247** Quick release mounting kit, 360° swivelling, that allows the mounting of GPS or Fishfinder. Supplied with fixing screws.

##### SPARE BASE

##### Technical features

Dimensions	60 x 90 mm
------------	------------

**142419** Quick release base for deck or wall mounting.

### RADIOS AND CASES

#### BOSS MARINE MR632UAB RADIO WITH BLUETOOTH

Marine FM/AM receiver with USB and AUX inputs, placed on the front for an immediate connection and at the same time protected by a rubber cover. Studied for whom is used to do internet streaming with the smartphone, since it includes **Bluetooth** connectivity with A2DP protocol to grant an optimal streaming from Spotify, Pandora, Rhapsody, Google Music, Apple Music, MySpace etc. apps. Moreover it is equipped with voice speaker to efficiently reply to eventual calls even during music listening.

The SD CARD slot is under the removable frame for a better protection of this part.

The stereo was suitably deprived of CD player, to create a completely solid product, that is with no mechanical parts to better counter the marine agents and to ensure a longer life.

##### Technical Features

Compatibility	USB - SD Card - AUX
Power	50 W x 4 channels
Compatibility	ID3 - Tag
Outputs	2 pre amp outputs 2 audio RCA

**629065** Boss Marine FM/AM MR632UAB radio with **Bluetooth** receiver. Wireless remote control included.



CE

#### BLUETOOTH BT08 AM/FM, MP3 AND USB RECEIVER

BT08 is a **WATERPROOF** dash stereo with black grill and green backlighting. Circular and innovative design which suits the aesthetic lines of the other control boards instrumentations. Equipped with the universal AUX audio input, compatible with any smartphones and MP3 plays. Thanks to its **Bluetooth** connectivity it's possible to shuffle all the tracks on your smartphone or MP3 player, otherwise you may use the USB port with any player, or the AUX input. Provided with RCA output.

USB and AUX are situated on the back of the stereo, but they can be moved onto the console through the optional accessory (item 629570 of our catalogue). Antenna not included (see our item 629098 optional).

Supplied with screws, connection cables and mounting bracket.

**Tested in compliance with European CE and RoHS regulations.**

##### RADIO STEREO


##### Technical Features

Compatibility	USB - BLUETOOTH - MP3 - AUX
Power	40 W x 4 canali
Display	green backlighting
Waterproofness	IP66
Radio external diameter	105 mm
Radio recess diameter	79,9 mm
Radio depth	41 mm

**629535** Bluetooth BT08 AM/FM, MP3 and USB receiver.

#### CONTROL BOARD CABLE WITH AUX AND USB PORT

**629570** AUX and USB port cable to access the USB and AUX ports when they are on the back of the stereo. Length 1 m.



### BLUETOOTH H820 AM/FM, MP3 AND USB RECEIVER

H820 is an in-dash **WATERPROOF** radio with burnished chromed frame and blue backlighting. Circular and innovative design that follows the aesthetic lines of the other dashboard instruments. Provided with universal AUX input compatible with any smartphone and MP3 players. Thanks to its **Bluetooth** connectivity, it is possible to shuffle through all the tracks on your smartphone or MP3 player, otherwise you may use the USB port with any player, or the AUX input. Equipped also with RCA output.

USB and AUX are situated on the back of the stereo, but they can be moved onto the console through the optional accessory (item 629570 of our catalogue). Antenna not included (see our item 629098 optional).

Supplied complete with screws, connecting cables and mounting bracket.

**Tested in compliance with European CE and RoHS regulations.**

**RADIO STEREO**

#### Technical Features

Compatibility	USB - BLUETOOTH - MP3 - AUX
Power	45 W x 4 channel
Display	backlighted blue colour
Waterproofness	IP66
Radio external diameter	113 mm
Radio recess diameter	88,12 mm
Radio depth	70 mm

**629536** Bluetooth H820 AM/FM, MP3 and USB receiver.

#### CONTROL BOARD CABLE WITH AUX AND USB PORT

**629570** AUX and USB port cable to access the USB and AUX ports when they are on the back of the stereo.  
Length 1 m.

### BLUETOOTH H833 AM/FM, MP3 AND USB RECEIVER

H833 is an in-dash **WATERPROOF** radio with chromed frame and blue backlighting. Circular and innovative design that follows the aesthetic lines of the other dashboard instruments. Provided with universal AUX input compatible with any smartphone and MP3 players. Thanks to its **Bluetooth** connectivity, it is possible to shuffle through all the tracks on your smartphone or MP3 player, otherwise you may use the USB port with any player, or the AUX input. Equipped also with RCA output.

USB and AUX are situated on the back of the stereo, but they can be moved onto the console through the optional accessory (item 629570 of our catalogue). Antenna not included (see our item 629098 optional).

Supplied complete with screws, connecting cables and mounting bracket.

**Tested in compliance with European CE and RoHS regulations.**

**RADIO STEREO**

#### Technical Features

Compatibility	USB - BLUETOOTH - MP3 - AUX
Power	45 W x 4 channel
Display	green backlighting
Waterproofness	IP66
Radio external diameter	113 mm
Radio recess diameter	94,5 mm
Radio depth	70 mm

**629537** Bluetooth H833 AM/FM, MP3 and USB receiver.

#### CONTROL BOARD CABLE WITH AUX AND USB PORT

**629570** AUX and USB port cable to access the USB and AUX ports when they are on the back of the stereo.  
Length 1 m.



## BLUETOOTH H301 VIDEO MP4, AM/FM, MP3 AND USB RECEIVER

The best of the range is the in-dash stereo mod. H301: **WATERPROOF** with chromed frame and built-in TFT 3" TFT display. Circular and innovative design that follows the aesthetic lines of the other dashboard instruments. Provided with universal AUX input compatible with any smartphone and MP3 players. Thanks to its **Bluetooth** connectivity, it is possible to shuffle through all the tracks on your smartphone or MP3 player, otherwise you may use the USB port with any player and to watch at the videos MP4 format and AUX input. Provided with RCA output and 1 video in and output. USB and AUX are situated on the back of the stereo, but they can be moved onto the console through the optional accessory (item 629570 of our catalogue). Antenna not included (see our item 629098 optional). Supplied complete with screws, connecting cables and mounting bracket. **Tested in compliance with European CE and RoHS regulations.**

### RADIO STEREO - VIDEO

#### Technical Features

Compatibility	MP4 Video - USB - BLUETOOTH - MP3 - AUX
Power	45 W x 4 channel
Display	3"
Waterproofness	IP66
Radio external diameter	113 mm
Radio recess diameter	89,50 mm
Radio depth	72,75 mm

**629538** Bluetooth H301 VIDEO MP4, AM/FM, MP3 and USB receiver.

### CONTROL BOARD CABLE WITH AUX AND USB PORT

**629570** AUX and USB port cable to access the USB and AUX ports when they are on the back of the stereo. Length 1 m.



## TRAY

### GLASS HOLDER WITH BASE

#### GLASS HOLDER

##### Technical features

Internal diameter	65 mm
-------------------	-------

**601203** White ABS glass holder with quick release base. Supplied with fixing screws.

#### SPARE BASE

##### Technical features

Dimensions	60 x 90 mm
------------	------------

**142419** Quick release base for deck or wall mounting.



### CHARTING ACCESSORIES

#### 777 PORTS AND ANCHORAGES



Publications containing plans for the coast with specified technical information: useful contacts for marine and harbor offices, service points and mooring modes, procurements.  
Volumes A4 format with colour picture pages and paperback binding.

	Type	Harbours and Anchorages	N° charts	N° nautic plans
551380	IONIAN - ADRIATIC VENICE GULF	From Punta Pellaro (RC) To Valle San Bartolomeo (Trieste)	44	188
551383	TYRRHENIAN SEA - LIGURIAN SEA Flegree and Pontine Islands Tuscan archipelago	From Balzi Rossi (IM) To Reggio Calabria (RC)	100	420
551390	SICILY AND ARCHIPELAGOS Aeolian - Aegadian - Pelagie Islands	Island circumnavigation	89	400
551393	SARDINIA AND CORSE	Island circumnavigation	107	435
551420	ISTRIA AND DALMATIA SLOVENIA AND CROATIA MONTENEGRO - ALBANIA	Punta Sottile - Muggia (IT) Butrinto (AL)	111	804
551426	GREECE from Albanese borders to Antipaxos	Albanian border to the Gulf of Ambracia, Diapontie Islands, Corfu, Paxos and Antipaxos	51	169
551427	GREECE rom the Lefkada Channel to Zakynthos	Lefkada Canal at the entrance to the Gulf of Patras, Lefkas, Ithaca, Kefalonia and Zakynthos	59	171

## LIFE JACKETS MED APPROVED

### LIFE JACKETS MED - IMO MSC 200 (80) APPROVED

Life jackets MED homologated in compliance with RES. IMO MSC 81(70) – MSC 200(80) – MSC 207(81) – LSA CODE AS AMENDED, MARINE EQUIPMENT DIRECTIVE (MED) 2014/90/EU.

The new generation of life jackets produced according to the latest standards in terms of passengers transport, (cruise and ferries) and for goods transport (container, bulk&liquid). Highly performing with a particular design, this product has an excellent floating grade and rotation. Easy to wear and to store on board. **COMPULSORY ON BOARD OF ALL EUROPEAN COMMUNITY MERCHANT SHIPS.**

	Size	Person weight Kg
<b>496770</b>	Baby	-15
<b>496771</b>	Teenagers	16 - 40
<b>496772</b>	Adults	40+



## BEACH EMERGENCY EQUIPMENT

### MAN OVERBOARD RESCUE SLING

- 496800** Man overboard rescue sling for beach resorts and swimming pools.



### LIFE RING HOLDER FOR LIFE GUARD DISTRICT

#### CONTAINER

- 495220** Container for life ring holder designed to be used in beach resorts, swimming pools and marinas. Ideal for our "MAGNUM" life ring our item 497021 and our regular rope item 523631.

#### BRACKET

#### Technical features

Height	150 cm
Tube diameter	40 x 60 mm
Base dimensions	300 x 300 mm
Base holes diameter	12 mm

- 495221** Bracket made of galvanised steel for lifering holder our item 495220.



## NATIONAL AND NAVIGATION FLAGS



### SIGNAL FLAG

Signal flag 100% polyester bunting.  
On request this flag can be customized.

Colour	20 x 30 cm	Dimensions		Signal	
		30 x 45 cm	40 x 60 cm		
○ white	<b>501298</b>	<b>501299</b>	<b>501300</b>	-	weather conditions safe for bathing
● yellow	<b>501302</b>	<b>501303</b>	<b>501304</b>	the boat has to clear custom controls	wind from mainland and presence of lifeguard
● red	<b>501306</b>	<b>501307</b>	<b>501308</b>	-	adverse weather conditions with banned bathing

## ACCESSORIES FOR TRAILERS



### LAMPS FOR TRAILERS

	Fig.	Model	Dimensions
<b>751180</b>	A	Side marker with orange reflector	112 x 40 x 25
<b>751183</b>	B	Rectangular side end-outline lamp white/red colour with bracket	128 x 53 x 37
<b>751193</b>	C	Number plate lamp	94 x 52 x 52
<b>751190</b>	D	Number plate lamp	82 x 30 x 33
<b>751185</b>	E	Front white lamp with reflector	65 x 63 x 42
<b>751186</b>	F	Front orange lamp with reflector	65 x 63 x 42

## STAINLESS STEEL ROD HOLDERS

### ADJUSTABLE S.STEEL ROD HOLDER

#### Technical features

Rod holder's internal diameter	42 mm
Rod holder length	250 mm
Total length	655 mm
Side rod holders inclination	20°
External diameter of inserting pipe	38 mm

**142295 STAINLESS STEEL** 3-rod rack 360° adjustable with strap and safety snap hook.



### HANDRAIL ROD HOLDER MADE OF STAINLESS STEEL AISI 316

**142297 STAINLESS STEEL AISI 316** rod holder with adjustable clamp, suitable for handrail mounting.



## S.STEEL WALL ROD HOLDER

### Technical features

Internal diameter	42 mm
Total length	250 mm

- 142287** STAINLESS STEEL AISI 316 rod holder for wall mounting complete with 2 mounting brackets.



## ABS FISHING ROD HOLDERS

## PIVOTING ROD HOLDER

### FISHING ROD HOLDER

### Technical features

Internal diameter	40 mm
Rod holder length	310 mm
Total height	400 mm
Encumbrance diameter	300 mm

- 142403** 4-rod rack, pivoting at 360°, white ABS with quick release base. Equipped with inserts for other fishing equipments and glass holder. Supplied with fixing screws.

### SPARE BASE

### Technical features

Dimensions	60 x 90 mm
------------	------------

- 142419** Quick release base for deck or wall mounting.



## MOUNT WITH QUICK RELEASE BASE

### BRACKET


- 142405** Mount with quick release base for rod holder's installation. Supplied with fixing screws.

### SPARE BASE

### Technical features

Dimensions	60 x 90 mm
------------	------------

- 142419** Quick release base for deck or wall mounting.



## DOUBLE REGULATION ROD HOLDER

### FISHING ROD HOLDER

### Technical features

Internal diameter	50 mm
Length	225 mm

- 142418** Nylon high resistance rod holder with rod lock ring, quick release base and mounting screws. Equipped with double adjustment: pivoting at 360° horizontally and 90° vertically.

### SPARE BASE

### Technical features

Dimensions	60 x 90 mm
------------	------------

- 142419** Quick release base for deck or wall mounting.





### BASE

#### Technical features

Dimensions 60 x 90 mm

**142419** Quick release base for deck or wall mounting.



### LURE RACK WITH SUCTION CUPS MOUNT

#### Technical features

Length 306 mm

Width 59 mm

Height 81 mm

**644750** Lure rack with suction cups for wall mounting.



### LURE RACK WITH QUICK RELEASE MOUNT

#### Technical features

Length 306 mm

Width 58,5 mm

Height 83,1 mm

**644751** Lure rack with suction cups and quick release for wall mounting.

## ENGINE MAINTENANCE



### VISION WINTER

#### WINTER WINDSHIELD FLUID -20°C.

Winter windshield fluid ready to use, recommended for ice protection until -20°C.  
Methanol-free formula : cleans and degreases improving visibility and preventing limescale.  
It dries quickly.  
Compatible with rubber, varnishes and with windshield wipers rubber.

**439141** Vision Winter 5 lt.  
Packing 4 pcs.

## BRUSHES, BUCKETS AND SPRAYERS



### COMFORT WASH PAD

#### Technical Features

Dimensions 245 x 135 mm

**595456** The "Comfort Wash Pad" is the new high quality microfiber pad that attracts and removes stain protecting the surfaces.  
It is composed of different types of microfiber:  
- Long pile side in chenille microfibre for a deep and accurate initial wash, optimal as a first step to deal with the most stubborn dirt and remove it from small cracks and all bodywork.  
- Short pile side ideal for general dirt and wash finishing, consisting of thousands of fine fibres capable of holding a large amount of water/shampoo solution.  
Packing 12 pcs.

## ACCESSORIES FOR MAINTENANCE

## ROLLER FOR ANTIFOULING APPLICATION


Microfiber roller frame with anti-drop high absorbency handle.

## FRAME WITH NAP ROLLER

	Roller length mm
<b>472561</b>	100
<b>472562</b>	120

## SPARE ROLLER

Spare nap rollers sold in pair.

	Roller length mm	
<b>472565</b>	100	pc
<b>472566</b>	120	2



## ADHESIVE AND ANTI-SLIP TAPES

## RIFÀTTUTTO TAPE

## RESISTANT LIKE STEEL IN A FEW MINUTES

Fiberglass cloth and polyurethane tape, for emergency or definitive rigid repairs. It hardens in 15/30 minutes and once completely polymerized, it can be pierced, sanded, grinded, polished and painted.

It sticks to any material: metals, cast iron, wood, glass, stone, marble, plastic, rubber, ceramic, PVC, polyester, nylon, fiberglass and cement (even between different material).

Resistant and stable until 150° C.

## Technical features

Tape height	5 cm
Tape length	130 cm

- 461100** Rifattutto Tape, composed of:
- 1 fiberglass bendage
  - 1 vinyl tape
  - 1 pair of gloves
  - Sand paper
- 12 pcs package.



## RIFÀTTUTTO STEEL REINFORCED EPOXY SEALANT

Bi-component epoxy steel-reinforced sealant for universal use, easy to use thanks to its ready-to-use dosage. It seals, moulds, glues, reconstructs, repairs, fills, plasters, **it hardens even underwater, in a few minutes**: wood, stone, plastic, metal, PVC, ABS, cement, ceramic, glass, cast iron, fiberglass, aluminium, nylon, marble etc.

When hardened RIFÀTTUTTO can be pierced, sanded, polished, planed, cut and painted, thus offering an optimal resistance to solvents, fuel, salt water, saline fog and humidity.

- 461101** Rifattutto 56 g. sealant.  
12 pcs package.





## GENERAL SALE TERMS

### 1) GENERAL SALE TERMS

The general sale terms can be modified or updated by G.F.N. due to new laws and regulations.

### 2) DESCRIPTIVE AND ILLUSTRATIVE PRODUCTS DESCRIPTIONS

**The colours, pictures, descriptive information and technical features of the products included in this catalogue and website, are not part of the contract, but have only indicative value and cannot be binding for eventual claims.**

**G.F.N. reserves the right to make any change, at any time, to the products and to their technical features with the purpose to improve the production.**

**The possible publishing and use of photographic material of G.F.N.'s property must be authorised exclusively through a letter signed by the management.**

### 3) ORDERS

The customer, sending the order, hereby implicitly accepts these terms of sale, and knows the characteristics, the proper use of the required products. To avoid misunderstandings, we recommend the customers to send written orders specifying:

1. Product code
2. Product description
3. Quantity

The terms proposed by our agents and representatives are subject to our approval. Agreements and arrangements with agents, brokers, and, generally, with GFN's staff, have value only of negotiations except seller's approval. GFN cannot be considered bound to what is included in the order's form if the same is not signed by the person entitled by the company. Subscriptions, signatures or initials of persons not entitled can only attest the terms of the proposals. Orders will be dispatched according to the availability of the moment, eventual backorder will be sent, unless otherwise ordered, as soon as possible, carriage forward or together with a new order according to the current price list.

Orders below € 100,00 net of any discounts VAT and fees, will be charged with fixed operating cost € 10,00.

All orders below € 100,00 net will be dispatched cash on delivery.

### 4) PRICES

Prices submitted by G.F.N. are the current ones at the moment of the order and can be updated until the moment of the shipment. They are intended to be net of taxes, extra fees (transport costs – package costs – insurance costs), custom duty and other financial costs. They are not binding and are communicated as informing purpose.

### 5) PACKING

The packing is charged at cost.

### 6) DELIVERY AND SHIPMENT TERMS

Goods are sold ex works delivery our warehouse in Campodarsego.

Goods travel at the Purchaser's risk who at the moment of shipment, assumes all risks relating to the goods sold.

Delivery terms are based on production and sale programs of the Seller and, therefore, are intended to be always indicative and never binding. The possible failure to meet the delivery deadlines will never be responsibility of the Seller, and won't give the right to the Purchaser to delay and/or suspend payments or ask for any compensation for damages. The Purchase quits every demand of essentiality of the delivery term.

**All the shipments, in Italy by truck, if sent with our transport companies, are warranted by G.F.N., against risks of lost, damages, etc. To make this valid, at the moment of the receipt of the goods in case of missing, damaged, or opened items, the acceptance must be done "WITH RESERVE". After verification of the damage, the purchaser must notify the same, within 3 (THREE) days from receipt, enclosing copy of the signed document. The non-observance of the above instructions will cause the forfeiture of the right.**

In case of shipment done by a transport company chosen by the Purchaser, goods travel at consignee's risk and in case of claims those must be done by the customer to his own forwarder.

G.F.N. has however the right not to fulfil the order, although it has been confirmed, if the Purchaser is insolvent in relation to other deliveries or towards other suppliers or in case he can no more offer financial guarantees.

### 7) PAYMENTS

Only in advance through bank transfer. Other different payment methods, subsequent to the first one, must be authorized and agreed through written agreement. In case of unpaid invoices or delayed payment default interests shall be charged since the day of default until the day of effective payment according to the rate stated by the Legislative Decree 231 of 09/10/2002.

Banks:

#### **INTESA SAN PAOLO - Agency of Campodarsego**

Via Antoniana, 220/D - 35011 CAMPODARSEGO (PD)

**IBAN: IT 23 M 03069 62422 074000969760**

Code BIC - SWIFT: BCITITMM

#### **UNICREDIT**

Via Caltana, 4 - 35011 CAMPODARSEGO (PD)

**IBAN: IT 96 Y 02008 62420 000040248744**

Code BIC - SWIFT: UNCRITM1S35

### 8) PROPERTY RIGHTS

In any case of instalment payment, the sale is done at G.F.N.'s property right until the last instalment of the price has been paid in accordance with clauses 1523 and further amendments; the Purchaser, however, has to bear the risks from the time of goods delivery. In case of non-payment of one instalment whose amount exceeds the eighth part of the full price, in other words of two instalments of any amount, the agreement is intended to be automatically cancelled because of Purchaser's non - fulfilment, with the right to receive immediately the goods back, with further compensation in case of damages and claims. Until the total amount is paid, therefore, the purchaser cannot transfer the goods, without the seller's confirmation, otherwise the agreement will be cancelled with the same consequences as above explained.

In case the goods are subject to foreclosure or other legal actions by third parties, the purchaser has to inform the seller immediately, for his rights protection.

### 9) SAMPLES

The samples of goods are always debited.

### 10) RETURN OF PRODUCTS

**Possible return of products have to be previously authorized by G.F.N.:** the request must be submitted in writing by means of the special form (that can be downloaded from the reserved area of our web site) and have to include in detail the noticed defect as well as all relevant information contained in the purchase invoice.

If the return request is accepted, GFN will give a RMA number: this number must be written down on the delivery note **otherwise the return of products will be rejected.**

The return must be done within one month from the RMA receipt, carriage paid delivery. **The returned products must be sent in their original packing, have not to have been used or damaged.** As refund 10% of the goods value (min.€ 5,00) will be charged, and possible extra fees can be added in case of product's restoring.

**Claims are not accepted after 8 days from the delivery date, moreover they have to be done only in case of real defects of the products. For this reason we strongly recommend our customer not to replace goods to final users without our authorization.**

### 11) JURISDICTION AND APPLICABLE LAW

For any controversy the qualified Court is that of Padova and the buyer-seller relationship shall be exclusively regulated by the Italian law.

DISCOVER THEM  
ALSO ONLINE



**G.F.N. SRL**

**GIBELLATO**  
FORNITURE NAUTICHE

[www.gfn.it](http://www.gfn.it)

Via Frattina 3 - 35011 Campodarsego PADOVA - ITALY  
Cod. Fisc. e Part. Iva : IT 02322290285  
Tel. +39 049 9200196 - Fax +39 049 5564050 - [info@gfn.it](mailto:info@gfn.it)